

Advantech Panel PCs

Diverse offerings for a wide range of applications

- Introduction
- Benefits and Features
- Selection Guide



ADVANTECH

Enabling an Intelligent Planet

www.advantech.com

Regional Service & Customization Centers

China Kunshan
86-512-5777-5666

Taiwan Taipei
886-2-2792-7818

Netherlands Eindhoven
31-40-267-7000

Poland Warsaw
00800-2426-8080

USA Milpitas, CA
1-408-519-3898

Worldwide Offices

Greater China

China
Toll Free 800-810-0345
Beijing 86-10-6298-4346
Shanghai 86-21-3632-1616
Shenzhen 86-755-8212-4222
Chengdu 86-28-8545-0198
Hong Kong 852-2720-5118

Taiwan
Toll Free 0800-777-111
Neihu 886-2-2792-7818
Xindian 886-2-2218-4567
Taichung 886-4-2329-0371
Kaohsiung 886-7-229-3600

Middle East and Africa

Israel 072-2410527

Asia

Japan
Toll Free 0800-500-1055
Tokyo 81-3-6802-1021
Osaka 81-6-6267-1887
Nagoya 81-52-856-9657

Korea
Toll Free 080-363-9494
Seoul 82-2-3663-9494

Singapore
Singapore 65-6442-1000

Malaysia
Kuala Lumpur 60-3-7725-4188
Penang 60-4-537-9188

Thailand
Bangkok 66-2-540-2299

India
Bangalore 91-80-2545-0206
Pune 91-20-3948-2075

Indonesia
Jakarta 62-21-751-1939

Australia
Toll Free 1300-308-531
Melbourne 61-3-9797-0100

Europe

Germany
Toll Free 00800-2426-8080/81
Munich 49-89-12599-0
Düsseldorf 49-2103-97-855-0

France
Paris 33-1-4119-4666

Italy
Milano 39-02-9544-961

Benelux & Nordics
Breda 31-76-523-3100

UK
Newcastle 44-0-191-262-4844
London 44-0-870-493-1433

Poland
Warsaw 48-22-31-51-100

Russia
Moscow 8-800-555-01-50
St. Petersburg 8-800-555-81-20

Czech Republic
Ústí nad Orlicí 420-465-521-020

Ireland
Oranmore 353-91-792444

Americas

North America
Toll Free 1-888-576-9668
Cincinnati 1-513-742-8895
Milpitas 1-408-519-3898
Irvine 1-949-420-2500
Ottawa 1-815-434-8731

Brazil
Toll Free 0800-770-5355
São Paulo 55-11-5592-5355

Mexico
Toll Free 1-800-467-2415
Mexico City 52-55-6275-2727



IBCON

ADVANTECH

Enabling an Intelligent Planet

www.advantech.com

Please verify specifications before quoting. This guide is intended for reference purposes only. All product specifications are subject to change without notice.

No part of this publication may be reproduced in any form or by any means, electronic, photocopying, recording or otherwise, without prior written permission of the publisher.

All brand and product names are trademarks or registered trademarks of their respective companies. © Advantech Co., Ltd. 2016

Buy Now



8600000327

Model	PPC-3060S	PPC-3100S/3120S/3150S			PPC-3100/3120		PPC-3150/3170/3190		
									
CPU	Intel® Celeron N2807 (1.58 GHz)	Intel® Celeron N2930 (1.86 GHz)			Intel® Atom™ D2550 (1.86 GHz)		Intel® Atom™ E3845, (1.91 GHz)		
Memory	1 x SODIMM DDR3L (up to 4 GB)	1 x SODIMM DDR3L (up to 8 GB)			1 x SODIMM DDR3 (up to 4 GB)		1 x SODIMM DDR3L (up to 8 GB)		
Display Size	6.5"	10.4"	12.1"	15"	10.4"	12.1"	15"	17"	19"
Max. Resolution	640 x 480	800 x 600	1024 x 768	1024 x 768	800 x 600	1024 x 768	1024 x 768	1280 x 1024	1280 x 1024
Luminance (cd/m ²)	700	400	500	400	400	600	400	350	350
Touchscreen	5-wire resistive	5-wire resistive, (optional) PCT multi-touch			5-wire resistive		5-wire resistive		
Network (LAN)	2 x GbE (Intel® I211)	2 x GbE (Intel® I211)			2 x GbE		2 x GbE (Intel® I210)		
I/O	1 x RS-232, 1x RS-232/422/485 (by BIOS) 2 x USB 2.0, 1 x USB 3.0	1 x RS-232, 1x RS-232/422/485 (by BIOS), 2 x USB 2.0, 1 x USB 3.0			3 x RS-232, 1 x RS-232/422/485 (by BIOS), 4 x USB 2.0 1 x Line-Out, 1 x Mic-In, 1 x VGA, 1 x GPIO,		1 x isolated RS-422/485, 4 x RS-232 (2 x by optional module), 1 x GPIO (8 channels, TTL level), 1 x USB 3.0, 3 x USB 2.0, 1 x VGA, 1 x DP1.1a, 1 x Line-Out, 1 x Mic-In		
Storage	(optional) 1 x 2.5" SATA bay, 1 x mSATA bay	(optional) 1 x 2.5" SATA bay, 1 x mSATA bay			1 x 2.5" SATA bay, 1 x mSATA bay		1 x 2.5" SATA bay, 1 x mSATA bay		
Expansion Slots	N/A	N/A			(optional) 1 x PCIe x1 or PCI for PPC-3120		1 x PCI or PCIe x1		
Additional Expansion	1 x Full-size Mini PCIe	1 x Full-size Mini PCIe			1 x Full-size Mini PCIe		1 x Full-size Mini PCIe, (optional) 1 x Cfast card,		
Input Power	12 ~ 24 VDC	12 ~ 24 VDC			12 ~ 30 VDC		9 ~ 32 VDC		
Mount Options	Panel, VESA 75	Panel, VESA 75			Panel, VESA 75		Panel, VESA 75		
Operating Temperature	0 ~ 50 °C with SSD	0 ~ 50 °C with SSD			0 ~ 50 °C		-20 ~ 60 °C with SSD		
Dimensions (mm)	198 x 151 x 41	272 x 217 x 46	317 x 246 x 49	392 x 313 x 52	275 x 220 x 65	325 x 254 x 59	397 x 318 x 66	442 x 362 x 70	459 x 384 x 68
Weight	1.5 kg	1.9 kg	2.1 kg	4 kg	2.5 kg	3.3 kg	5.3 kg	6.3 kg	7.9 kg
Operating System	Win 7/8.1/10, WEC 7, Linux, Android	Win 7/8.1/10, WEC 7, Linux, Android			Win XP, Win 7 (32 bit), WEC 7, Linux		Win 7/8.1/10, WEC 7, Linux		

Model	PPC-3151	PPC-4151W/4211W		PPC-6120	PPC-6151C
					
CPU	6th Gen Intel® Core™ i5-6300U	4th Gen Intel® Core™ i5-4300U/i3-4010U		4th Gen Intel® Core™ i/Celeron® processor	Supports processors with up to 45 W TDP
Memory	1 x SODIMM DDR4 (up to 16 GB)	1 x SODIMM DDR3L (up to 8 GB)		2 x SODIMM DDR3 (up to 8 GB per SODIMM)	Dependent on the MB specifications
Display Size	15"	15.6"	21.5"	12.1"	15"
Max. Resolution	1024 x 768	1366 x 768	1920 x 1080	1024 x 768	1024 x 768
Luminance (cd/m ²)	400	400	300	600	400
Touchscreen	5-wire resistive or PCT multi-touch	5-wire resistive or PCT multi-touch		5-wire resistive	5-wire resistive
Network (LAN)	2 x GbE (Intel® I211-AT, I219LM)	2 x GbE (Intel® I211-AT, I218LM)		2 x GbE	Dependent on the MB specifications
I/O	1 x isolated RS-422/485, 4 x RS-232 (2 x by optional module), 1 x GPIO (8 channels, TTL level), 4 x USB 3.0, 1 x VGA, 1 x DP1.2, 1 x Line-Out, 1 x Mic-In	1 x isolated RS-422/485, 4 x RS-232, 4 x USB 3.0 at rear, 1 x USB 2.0 at right side 1 x VGA, 1 x DP1.2 1 x Line-Out, 1 x Mic-In,		1 x isolated RS422/485, 4 x RS-232, 4 x USB 3.0, 4 x USB 3.0, 1 x DP1.2, 1 x VGA, 1 x Line-Out, 1 x Mic-In	4 x Reserved ports 2 x WLAN antenna ports
Storage	1 x 2.5" SATA bay, 1 x M.2 bay (22 x 42 mm)	1 x 2.5" SATA bay, 2 x 2.5" SATA bay, 1 x mSATA bay 1 x mSATA bay		1 x 2.5" SATA bay, 1 x mSATA bay	1 x 2.5" SATA bay, or 2 x 2.5" SATA bay
Expansion Slots	1 x PCIe x4 or PCI	1 x PCIe x4 or PCI		(optional) 1 x PCIe x4 or PCI	2 x PCI or 1 x PCIe x 4
Additional Expansion	1 x Full-size Mini PCIe, (optional) 1 x Cfast card,	1 x Full-size Mini PCIe		1 x Full-size Mini PCIe	Dependent on the MB specifications
Input Power	9 ~ 32 VDC	9 ~ 32 VDC	12 ~ 32 VDC	12 ~ 30 VDC	100 ~ 240 VAC @ 50/60 Hz
Mount Options	Panel, VESA 75	Panel, VESA 100	Panel, VESA 75/100	Panel, VESA 75	Panel, (optional) VESA 75/100
Operating Temperature	0 ~ 50 °C with SSD	0 ~ 50 °C with SSD 0 ~ 50 °C		0 ~ 50 °C	0 ~ 50 °C
Dimensions (mm)	392 x 313 x 56	420 x 269 x 59	559 x 350 x 64	325 x 254 x 74	392 x 313 x 104
Weight	5.4 kg	5.69 kg	7.8 kg	3.8 kg	5.03 kg
Operating System	Win 7/8.1/10, Linux	Win 7/8.1/10, Linux		Win 7/8.1/10, Linux	Dependent on the MB specifications

Advantech's PPC Product Family

Reliable, Cost-Effective, and High-Performance Industrial Panel PCs

Advantech's PPC (panel PC) product family offers highly scalable, economical solutions in a range of performance classes that support various display sizes to satisfy diverse equipment manufacturing and process automation applications. The PPC product portfolio includes an all-in-one series (PPC-3000/3000S) and a customizable series (PPC-6000C). The all-in-one series features an optimized design, compact form factor, and industrial-grade specifications, such as rich I/O, flexible expansion slots, and a wide operating temperature range. Regarding the customizable series, these products are designed to be equipped with any mini-ITX motherboard according to price and functionality.

All-in-One Series

Advantech's PPC-3000/3000S series systems are equipped with a fanless, low-power Intel® Core™ i/Atom™ processor. The standard PPC model (PPC-3000 series) features rich I/O and expansion slots that enable system integrators to build complex systems. Meanwhile, the PPC-3000S series systems, which are aimed at industrial IoT applications, are ultra slim devices that feature a stylish appearance to ensure easy integration.

All-in-One

- Fanless
- Compact
- Low power consumption

intel Core i

intel Atom

Configurable Series

Compatible with diverse mini-ITX motherboards, the PPC-6000 series allows system integrators to configure the device according to their exact usage requirements. This flexibility and versatility makes PPC-6000 ideal for applications that require high-performance computing and multiple expansions, such as machine vision operations.

Configurable

- Fan
- High computing power
- Selectable motherboard

intel Core i

Features



IP65 true flat panel

In addition to IP65 certification for dust and water resistance, Advantech's panel PCs are equipped with a true flat P-CAP/resistive touchscreen, giving the system an elegant and stylish appearance.



Rich industrial-grade I/O

To ensure excellent connectivity for integrating devices and peripherals, Advantech's PPC systems are equipped with multiple industrial-grade I/O, including isolated RS-422/485, GPIO, RS-232, USB 3.0, DisplayPort, and Line Out ports.



Standard

- Rich I/O • Slim • Expandable • Wide temperature range

PPC-3001

PPC-4151W

- 6/4th Gen Intel® Core™ i processor
- PCT/resistive touchscreen
- PCIe x4/PCI expansion



Light

- Essential I/O • Ultra slim

PPC-3001S

- 6th Gen Intel® Core™ i processor
- PCT touchscreen
- All-metal body



PPC-3000

PPC-3170

- Intel® Atom™ E3845/D2550 processor
- Wide temperature -20 ~ 60 °C
- Resistive touchscreen
- PCIe x1/PCI expansion



PPC-3000S

- Intel® Atom™ N2930/N2807 processor
- PCT/resistive touchscreen
- All-metal body

PPC-3120



PPC-3100

PPC-6000C

- Compatible with various Mini-ITX MBs
- Supports CPUs with up to 45W TDP
- Resistive/PCT touchscreen
- PCIe x4/2 x PCI or PCIe x1




Expansion slots

PPC series systems feature expansion slots that support a range of optional riser cards, such as PCI, PCIe x1, and PCIe x4, to enable flexible expansion according to the platform specifications.



Wide operating temperature range

All PPC-3000 series systems equipped with an Intel® Atom™ processor support a wide operating temperature range of -20 ~ 60 °C, making them suitable for operation in harsh environments.




Wide input power range

With support for a wide input power range of 12 ~ 24 V_{DC}, Advantech PPC systems can be operated in various industrial environments without necessitating an additional power converter or generating increased energy costs.

t

- All-metal housing



All-metal body
PPC-3000S series products are designed with an all-metal body to ensure an elegant and streamlined appearance.

Accessories

PPC-IPS-AE



A lightweight, intelligent power management module that protects the system from electrical damage and reduces the potential for data losses. This module can serve as a temporary power source during short-term power outages and can ensure safe system shutdowns.



PPC-STAND-A1E

An elegant desktop stand made of aluminum alloy that supports VESA 75/100. This stand allows users to adjust the vertical viewing angle and can be affixed to surfaces using two screws.



PPC-ARM-A03

A swivel arm equipped with a C-clamp to enable installation on any surface. The swivel arm supports 360-degree rotation.



PPC-174T-WL-MTE

A compact wall-mount kit that supports 360-degree rotation and vertical/horizontal viewing angle adjustment.



PPC-WLAN-B1E

An optional Wi-Fi module with dual antennae and 802.11 a/b/g/n/ac support.